

Datasheet Conveyor Belt




**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
3 RF 12
- **Nitta Japan code:**



Construction: 3 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Fabric	
Thickness:	2		-	mm (approx.)
Colour:	Grey	Grey	-	
Hardness:	35 Shore A		-	
Profile:	-		-	

Total thickness:	4,9	mm (approx.)
Weight:	6,1	kg/m ² (approx.)
Max. width:	3000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	15	N/mm
Advised pretension:	5 - 8	N/mm
Maximum allowable tension:	29	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:		
Flexing:	100	mm
Backflexing:	150	mm

Special approval: Not applicable

Applications:
In the wood and board industry
High friction applications
Heavy duty applications

Date of issue 16-12-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com